

## STATEMENT OF CONFORMITY ISPM15

### Interpak Ltd. is a supplier / retailer of ISPM15 Crates

We hereby confirm that all Crates (Timber and Plywood construction) supplied by Interpak Limited fully comply to the regulations of ISPM15.

All Timber products used have been fumigated / Heat Treated in accordance with the regulations as follows:

All solid wood and wood packaging materials (WPM) over 6 mm in thickness used for export, such as wooden pallets, dunnage and crating, must be treated. In the heat treatment process, WPM must be heated until its internal temperature reaches 56 degrees Celsius or more for 30 minutes. This is regarded as the most effective and environmentally friendly way to destroy harmful pests contained in wood.

As fumigation becomes a less popular treatment option, others such as dielectric or microwave heating, as well as steaming and vacuuming, are being considered possible solutions. However, overall, heat treatment continues to be the industry practice.

After the wood is treated, it is stamped or branded with the internationally recognized IPPC mark. The treatment method used and country of origin of WPM is also indicated by the mark.

Signed .....

On Behalf of Interpak Ltd



All corrugated products and foam products are subject to the industry standard tolerance of + / - 10% on Quantity. This is due to the nature of the machinery used to produce the finished products - which can damage some product during conversion. To try and achieve your desired quantity - we always order 10% over on raw materials assuming a 10% damage potential. Any goods supplied within the 10% tolerance specified will be deemed good and Invoiced accordingly.

